

PRODUCT SPECIFICATIONS

Hammerglass Single



Hammerglass Single

Hammerglass Single is of a single ply construction supplied in different thicknesses for mounting/installing into existing framework and over glaze profiles. Ideal for older window frames in for example listed buildings and commercial properties etc.

With its unique tough, durable hard wearing surface Hammerglass single a popular choice for use in both the initial stages of new build design through to the replacement glazing.

Installing Hammerglass Single would mean no alterations to existing architecture.

Lightweight.

Recommended uses

Schools, shops, shopping malls, public buildings, office blocks, petrol stations, pharmacies, bus shelters, media display cabinets etc. or anywhere you want to protect against vandalism or break-ins.

Hammerglass Single can also be used as a traffic divider between lanes, as well as noise reduction barriers on roads and railways.

Product description

Compared to toughened or laminated glass, Hammerglass can be installed in reduced thickness which, in turn, reduces the overall product weight further.

Through its unique surface treatment, Hammerglass is resistant against chemicals and most acid attacks. This means that graffiti and other dirt can be removed with solvents or graffiti removal products. Single panes consist of 6, 8, 10, 12, 15, 17 or 20 mm Hammerglass.

Hammerglass does not contribute to the spread of fire in the event of fire.

Security Class and certificates

Hammerglass Single is approved according to EN 356 in the following security classes:

- 6 mm Hammerglass Single P7B
- 8 mm Hammerglass Single P8B (equivalent to Protection Level 3, the highest safety rating for antiburglary grilles and rolling shutters)
- Hammerglass is also certified according to British Police standards "Secured by Design"

Text proposal for product specifications

"The single glass pane is to be of type Hammerglass Single. Installation is to be done using Hammerglass recommended silicone for the best adhesion and durability."

Designation example: HmG06 Single (if 6 mm).

Laser marking

All Hammerglass panes are laser marked with logo and serial number.

Warranty

The warranty period against any degeneration or colour changes is 10 years .

Installing

Hammerglass is installed only by certified installers in order to guarantee the highest quality.

